



SAN Connectivity Kit Expansion Options

The storage area network configured with a SAN Connectivity Kit can be expanded to support additional servers and storage. The components you need to upgrade your SAN are listed below. Refer to an authorized QLogic distributor or storage solutions provider for up-to-date pricing information.

Items marked with an "*" are for SAN Connectivity Kits featuring SANbox 5600 or SANbox 5200 switches.

Description	Distribution SKU
4Gb Components	
Software license key to activate 4 additional switch ports*	LK5000-4PORT*
SANblade HBAs	<ul style="list-style-type: none"> > QLA2460-CK - 266MHz, PCI-X to FC, single port, multi-mode optic > QLA2462-CK - 266MHz, PCI-X to FC, dual port, multi-mode optic > QLE2460-CK - 2.5Ghz, PCI Express to FC, single port, multi-mode optic > QLE2462-CK - 2.5Ghz, PCI Express to FC, dual port, multi-mode optic
Small Form Factor Pluggables (SFP) 4Gb*	SFP4-SW-JD4 - 4-pack * SFP4-SW-JD5 - 5-pack *
XPAK 10Gb ISL Cables*	<ul style="list-style-type: none"> > XPAK-COPP-03* - 10Gb 3" (76mm) copper stacking cable with integrated XPAK connectors. > XPAK-COPP-09* - 10Gb 9" (228mm) copper stacking cable with integrated XPAK connectors. > XPAK-SW-01* - 10Gb (quantity 1) short-wave, 850nm XPAK optic with LC connector > XPAK-LW-01* - 10Gb (quantity 1) long-wave, 1310nm XPAK optic with SC connector
2Gb Components	
Software license key to activate 4 additional switch ports*	LK5000-4PORT*
SANblade HBAs	<ul style="list-style-type: none"> > QLA2310F-CK 64-bit, 66-MHz PCI-X to Fibre Channel optical media (single channel, full-height bracket) > QLA2340-CK 64-bit, 133-MHz PCI-X to Fibre Channel optical

	<p>media (single channel, full-height bracket)</p> <ul style="list-style-type: none"> > QLA2340L-CK 64-bit, 133-MHz PCI-X to Fibre Channel optical media (single channel, low-profile bracket) > QLA2342-CK 64-bit, 133-MHz PCI-X to Fibre Channel optical media (dual channel, full-height bracket) > QLA2342L-CK 64-bit, 133-MHz PCI-X to Fibre Channel optical media (dual channel, low-profile bracket) > QLA2344-CK 64-bit, 133-MHz PCI-X to Fibre Channel optical media (quad channel, full-height bracket)
Small Form Factor Pluggable (SFP) 2Gb (PicoLight)	SFP2-SW-03
Cables	
Dual LC to Dual LC fiber optic cable (10 meters)	CBL-LC-LC-10m
Dual LC to Dual LC fiber optic cable (5 meters)	CBL-LC-LC-5m
XPAK 10Gb ISL Cables*	<ul style="list-style-type: none"> > XPAK-COPP-03* - 10Gb 3" (76mm) copper stacking cable with integrated XPAK connectors. > XPAK-COPP-09* - 10Gb 9" (228mm) copper stacking cable with integrated XPAK connectors. > XPAK-SW-01* - 10Gb (quantity 1) short-wave, 850nm XPAK optic with LC connector > XPAK-LW-01* - 10Gb (quantity 1) long-wave, 1310nm XPAK optic with SC connector